

PLT13 REWIRABLE PLUG

⚠ PLEASE READ BEFORE USE



Do not drag adaptor along the







Do not leave adaptor "ON" when not in use.



Do not insert adaptor without aligning Locator to V-Groove.



Keep away from fire.



Keep away from water.



Not for outdoor use.




To be installed by a qualified electrician/ installer.

FITTED WITH BS 1362 13A FUSE ALWAYS FIT BS 1362 REPLACEMENT

CATRIDGE FUSE

Wiring Instruction

Prepare leads as shown:



Technical Specifications

Product Description Rated Voltage Rated Current

Frequency

Fused : Terminal Capacity (Live, Neutral and Earth): Ambient Operating Temp.

Rewirable Plug 250 V a.c. 13 Amp 50Hz/60Hz 13Amp Fuse 1.5mm² (3 Core cable)


-5°C to +40°C (Not to exceed an average of more than 25°C

in any 24 hours period)

Ordinary Polycarbonate Brass, Phosphors Bronze Estimated 75 grams

Material (Enclosure) Metal Components Material

User Instructions




Align Locator to V-Groove. Push in plug.

3



Turn plug 90° clockwise. ('Click' sound)



(LED indicator 'ON')

3 Years Limited Warranty

- Eubiq Pte Ltd ("Eubiq") warrants to the end-user of the ("the Customer") that the
 product will be free from defects in materials and workmanship under normal use for a period of three (3) years from the date of retail purchase by the original end-user purchaser ("Warranty Period").
- 2. The Customer should access and refer to Eubiq's website at www.eubiq.com for a list of Eubiq authorised dealers to contact for warranty service.
- All requests for warranty service must be made within the Warranty Period, and be accompanied by the original dated proof of purchase.

www.eubiq.com