



SK KITCHEN TRACK

ELECTRICAL

Rated Voltage	250V a.c. Single-phase
Rated Current	40Amp max
Frequency	50Hz / 60Hz
Conditional Short Circuit Rating	(MCB: In:40A Ue:400V), Type B (BS EN 60898-1) Prospective current: 6KA (BS EN 60439-2)
Conductor Resistance Line & Neutral	4.4 mohm/meter run
Conductor Impedance	4.5 mohm/meter run
Voltage drop: Line & Neutral Line & Earth	4.5 mVA/meter run 2.73 mVA/meter run
Rated Impulse Withstand Voltage	4000V a.c.
Connection of Adaptor or Tap-off Unit	Intended to be connected and disconnected when system is energized and with a load connected
Terminal Capacity: Live, Neutral & Earth	4.0 mm ² to 10 mm ²

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 35°C in any 24 hours period)
Maximum Installation Altitude	2000 meters
Resistance to Impact	Heavy Impact
Degree of Protection	IP4X
Degree of Pollution	2 (Non-conductive pollution with temporary conductivity caused by condensation)

MATERIAL

Track Material	Aluminium
Insulation Material	Polycarbonate

SIZE AND WEIGHT (Based On 1 meter Length)

Overall Dimension (Height x Depth x Width)	80mm x 26mm x 1000mm
Weight	Estimated 2.5 kilograms

Accessories	Kitchen Rail (Available standard length 400mm and 600mm) Single Kitchen Hook (H x W x D: 53mm x 35mm x 46mm)
Compliance	PSB test mark ASTA certified GOST.R certified IEC 61534-1:2003 / EN 61534-1
Guarantee	3 years subject to Eubiq Limited Warranty Statement



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.